







ABC is a flooring brand that is proudly made in Egypt I. It uses the best fiberboard and comes in a range of color and pattern options that all satisfy the highest requirements.

We think that the key to our success is quality. By collaborating with our sister businesses that specialize in printing, impregnation, and hot pressing, we are able to carefully manufacture our laminate flooring utilizing cutting-edge technology and high-quality materials. To make sure that every plank lives up to our high standards, we follow strict quality control guidelines. We make these planks using the best materials and the highest quality standards utilized in this business worldwide.

These planks are in direct competition with similar imported items made with the same components, manufacturing methods.



Panel build up

- 1. Wear and scratch-resistance layer
- 2. Decorative paper layer
- 3. Moisture-resistant wood core
- 4. Back balance layer



Panel Characteristics				
Width	187	mm.	+/- 0.1 mm.	EN 13329
Length	1194	mm.	+/- 0.5 mm.	EN 13329
Number of panels per pack	10	panels		
Thickness	9	mm.		
Tongue and groove	Double Click		+/- 0.17 mm.	EN 13329

General data (According to EN Standard)					
	Method	Parameters	^{tt} Norm. Requirements		
Abrasion resistance	EN 13329	AC3	≥ 2500		
Wear class	EN 13329	Agree	EN 13329		
Impact resistance	EN 13329	EN 13329	Small Ball /1600mm / LC1		
Scratch resistance	EN 13329	Free of changes	EN 13329		
Effect of a castor chair	EN 13329	Group 4	EN 13329		
Stain resistance	EN 13329	No change, Rate 5	Group 1 : 5		
Cigarette burn resistance	EN 438 - 2	Rate 5	EN 13329		
Straightness	EN 13329	0.29	≤ 0.30		
Sqaureness	EN 13329	< 18%	≤ 0.20		
Thickness Swelling	EN 13329	16.81%	≤ 0.18		